



RE WELD



info@rentease.co | www.rentease.co

RE MIG 200



Technical Specifications	RE MIG 200	Accessories
Voltage :	220V 50HZ	 3M 15AK MIG TORCH 2m 200A holder 2M 300A earth clamp 1PCS Teflon pipe U type wire roller brush&hammer plastic mask manual
MIG Output current range(A) :	40-200A	
LIFT TIG Output current range(A) :	15-180A	
MMA Output current range(A) :	20-180A	
Duty cycle T=25C°, (%) :	60	
U0, Rated no load voltage(v) :	55	
Insulation class :	H	
Protection class :	IP21S	
Power factor(cosφ) :	0.7	
Efficiency(%) :	85	
wire diameter MIG(mm) :	0.8/0.9.1.0mm	
Tungten diameter TIG(mm) :	1.6-3.2mm	
Welding rod diameter MMA(mm) :	1.6-4.0	
Quick joint :	35-50mm	

MAKE THE DIFFERENCE

RENT EASE

RENTEASE LIMITED

HEAD QUARTERS

Plan S Business Park, First Floor 103/104, Plot D 108/1,
Opposite D Y Patil Stadium, Navi Mumbai 400706,

Mobile: +91- 9699143372



support@rentease.co | www.rentease.co